SA POWERNET

400VA TRANSFORMER

TRA

COMPACT, RUGGED, INCREDIBLY TOUGH

Our SA POWERNET EX 400VA Transformer comprises a composite box mounted via shock absorbers onto a marine-grade steel frame, with a special internal chassis securing the internal components. The result is a phenomenally rugged unit, but with no compromise on portability at only 17kg and 560mm wide, it'll go anywhere you need it. A range of voltage and output options are available, as well as a Centre Tapped to Earth variant, it's supplied fully tested and ready for use.





- EX Certified for Zones 1 and 2 (gas). 21 and 22 (dust)
- INMETRO Certified
- Portable, tough, and durable
- Compact and lightweight
- Waterproof and dustproof
- Fuse protected



CORE PRODUCT INFORMATION

SA POWERNET EX Transformer 4-way 230-24V 400VA, c/w 1 x 16A CEAG plug, 4 x ATX sockets, and 15m of HOFR braided cable Order Code: TRA23024/400-4EX/CEA

110-24V 400VA, c/w 1 x 16A CEAG plug, 4 x ATX sockets, and 15m of HOFR braided cable Order Code: TRA11024/400-4EX/CEA

SA POWERNET EX Transformer CTE 4-way 230-110V 400VA, c/w 1 x 16A CEAG plug, 4 x CEAG sockets, and 15m of HOFR braided cable Order Code: TRAC230110/C400-4EX/CEA

SA POWERNET EX Transformer 4-way 230-42V 400VA, c/w 1 x 16A CEAG plug, 4 x CEAG sockets, and 15m of HOFR braided cable Order Code: TRA23042/C400-4EX/CEA



STAHL connectors and different cable lengths also available - please contact SA Equip for more details.

SPECIFICATIONS

CERTIFICATION ⟨€a⟩ II 2 G D Ex db eb IIC T4/T5 Gb Ex tb IIIC T135/100°C Db

INGRESS PROTECTION IP66

OPERATING TEMPERATURE -20°C to +40°C (Max 15A) -20°C to +50°C (Max 12A) -20°C to +55°C (Max 6A)

RATING 400VA

INPUT VOLTAGE 110VAC (16A Plug) 230VAC (16A Plug) 400VAC (32A Plug)

OUTPUT VOLTAGE 12VAC [4 x Socket outlets] 24VAC [4 x Socket outlets] 42VAC (4 x Socket outlets) 110VAC [4 x Socket outlets] 230VAC [4 x Socket outlets]

DIMENSIONS 560mm (w) x 460mm (d) x 300mm (h)

WEIGHT 17kg (without cable)

CABLE LENGTH 15m (or as required)



OWER